

BID #7334 – SPECIFICATION #1
MINIMUM SPECIFICATION FOR
(6) HONDA POLICE MOTORCYCLES
Class Code 01-18-12-G
9/29/09
ST1300PA: POLICE BIKE

SPECIFICATIONS CHECKLIST
(SUBMIT THE COMPLETED CHECKLIST WITH THE BID)

SCOPE

- A. It is the intent of this specification to describe a police motorcycle to be used in traffic and law enforcement work. It will be driven on all types of roads and road surfaces and must possess outstanding handling characteristics, maneuverability and stability.
- B. It is intended that the manufacturer in the selection of components will use materials and design practices that are the best available in the industry for the type of operating conditions to which the vehicle will be subjected. Engine, transmission, drive train, brake, suspension, wheel, tire and other component parts of the vehicle shall be selected to give maximum performance, service life and safety, not merely meet the minimum requirements of this specification.
- C. The term "heavy duty" as used in this specification, shall mean that the item to which the term is applied shall exceed the usual quantity, quality or capacity supplied with standard production vehicles; and it shall be able to withstand unusual strain, exposure, temperature, wear and use.
- D. Motorcycles offered in compliance with this specification must be factory-produced police models. Police accessories must be engineered and designed, or certified, by the manufacturer of the motorcycle to be compatible with all other components, give dependable service and not degrade its handling characteristics or appearance.

MINIMUM SPECIFICATION FOR
(6) HONDA POLICE MOTORCYCLES
Class Code 01-18-12-G
9/29/09
ST1300PA: POLICE BIKE

		<u>Per Spec</u>
MODEL:	Shall be 2009 or latest production model ST1300PA 2-wheel motorcycle equipped for police service Shall be equipped with a side/center stand	_____ _____
ENGINE:	Not less than 1261 cubic centimeter displacement Shall be V4 Shall produce not less than 125 bhp Crankshaft to be balanced at factory and engine shall be free from vibration during service life of motorcycle Shall be equipped with all standard accessories including air cleaner, oil filter, and latest-type fuel injection	_____ _____ _____ _____ _____
POWER TRAIN:	To be shaft driven	_____
TRANSMISSION:	Shall be minimum (5) speeds Gears shall be constant-mesh design Shift pattern shall be as follows: Neutral located between first and second gears Shall shift down from neutral to first gear by toe and up from neutral to second, third, fourth, etc. Shall have foot shift lever of rocker type and designed to be operated by toe Foot shift lever to be located on left side An indicator light, readily visible to the rider, shall be provided to indicate when the transmission is in neutral position	_____ _____ _____ _____ _____ _____ _____ _____
BRAKES:	ABS Front: Dual Disc Rear: Single Disc	_____ _____ _____
HANDLEBARS:	Handlebars shall be "Helibar" type with riser in order to position them up and back from the factory position.	_____
ELECTRICAL:	Shall be equipped with heated grips with thermostat control. Two (2,) 12 v dc power outlets mounted at rear of pocket as high as possible, one (1) each side and necessary harness for connections.	_____

MINIMUM SPECIFICATION FOR
(6) HONDA POLICE MOTORCYCLES
Class Code 01-18-12-G
9/29/09
ST1300PA: POLICE BIKE

		<u>Per Spec</u>
TIRES:	To be non-skid, minimum "V" speed rating, tubeless first-quality motorcycle tires designed to give best performance for police service	_____
	Tire size to be at least 18" front and 17" rear	_____
	Each tire and wheel assembly to be statically and dynamically balanced	_____
	Safety bead retention type	_____
WINDSHIELD:	To be of the latest type and design approved by the CA Highway Patrol	_____
	To be of clear plastic approved glazing material Lexan MR 4000	_____
	Mounted to appropriate frame mounted fairing	_____
	Shall be mounted in "breakaway" style in the event of a collision	_____
	Shall provide full vision	_____
	Shall not cause imbalance of the motorcycle at any speed	_____
	Shall be taller than standard factory windshield for improved wind clearance	_____
	Shall be adjustable for various rider height	_____
KEYS:	To have (3) sets of keys provided for each machine at time of delivery	_____
COLOR:	Appliance White or comparable with black trim	_____
RADIO BOX AND SADDLE BAGS:	Furnish and install brackets and saddlebags on each side of rear fender	_____
	Saddlebags shall be top opening if available or standard opening will be acceptable	_____
	Subject to inspection prior to approval by buyer	_____
	Radio box dimensions to be approximately 18" long, 7" wide x 9-1/2" deep	_____
LEGAL REQUIREMENTS:	The motorcycle shall in all respects meet or exceed all requirements of Federal Government Safety Standards for 2009 model motorcycles, the CA Administrative Code, the Health and Safety Code and the CA Air Resources Board	_____

MINIMUM SPECIFICATION FOR
(6) HONDA POLICE MOTORCYCLES
Class Code 01-18-12-G
9/29/09
ST1300PA: POLICE BIKE

Per Spec

PRE-DELIVERY SERVICE:

All motorcycles must be completely serviced, inspected properly, adjusted and road tested before delivery including the proper fill of all fluids and lubricants except gasoline

WARRANTY:

The standard manufacturer's warranty shall apply to all motorcycles purchased under this specification
The starting date of the warranty shall be the date the motorcycle is actually placed in service and not the delivery date

PERFORMANCE REQUIREMENTS:

Motorcycles purchased against this specification shall possess outstanding roadability, maneuverability, cornering and other handling characteristics necessary for a motorcycle engaged in traffic law enforcement which includes operation over various types of roads, road surfaces and operational conditions

TECHNICAL TRAINING: City of Anaheim motorcycle technician shall be provided Honda factory training on this motorcycle.

MANUALS:

One set of two service manuals and two parts manuals shall be provided at the time of delivery. C D ROM is an acceptable substitute for manuals.
Manuals are per purchase order not per motorcycle.

MINIMUM SPECIFICATION FOR
(6) HONDA POLICE MOTORCYCLES
Class Code 01-18-12-G
9/29/09
ST1300PA: POLICE BIKE

VENDOR DELIVERY DATE

Each bidder shall provide in the space noted below, the maximum number of calendar days, after the receipt of a purchase order, that will be required to deliver the vehicle or equipment as specified.

It is of utmost concern to the City of Anaheim that the bidder supplied delivery date be met. Any delays in the delivery date as quoted herein shall be immediately reported in writing to the purchasing agent with a copy to the requesting department representative. Any change in the original quoted delivery date is subject to approval by the City.

However, the City of Anaheim reserves the right to cancel the purchase order for non-performance of quoted delivery at no cost or obligation to the City.

Vendor Delivery _____

Authorized Representative _____

Date _____

DELIVERY

Deliver to 955 S. Melrose, Anaheim, CA 92805. The invoice and any necessary vehicle registration documentation and warranty information must accompany delivery.