



MINIMUM HALF-WIDTHS

	MINIMUM WIDTH OF STREET
PRIVATE STREET SERVING 4 UNITS OR LESS, PARKING NOT PERMITTED ON EITHER SIDE, SIDEWALK REQUIRED.	20'
PARKING NOT PERMITTED ON EITHER SIDE, SIDEWALK REQUIRED	28'
PARKING PERMITTED ON ONE SIDE ONLY, SIDEWALK REQUIRED	32'
PARKING PERMITTED ON BOTH SIDES, SIDEWALK REQUIRED	36'

NOTES:

1. THE USE OF PRIVATE STREETS SHALL BE LIMITED TO LOCAL INTERIOR RESIDENTIAL STREETS NOT CARRYING THROUGH TRAFFIC.
2. PRIVATE STREETS SHALL BE DESIGNED AND CONSTRUCTED IN ACCORDANCE WITH CITY STANDARDS AND SHALL BE REVIEWED AND APPROVED BY THE DEPARTMENT OF PUBLIC WORKS.
3. PAVEMENT SECTIONS SHALL BE DETERMINED BY SOIL "R" VALUE AND TRAFFIC INDEX AND SHALL BE SHOWN ON THE PROJECT PLANS.
4. MINIMUM PAVEMENT SECTION IS AS FOLLOWS:
 - A) PRIVATE STREET: 4" A.C. OVER 4" A.B.

REC'D		1/12/04	APP.	1-13-04		
	DEPUTY CITY ENGINEER	DATE	D.P.W. / CITY ENGINEER	DATE	REVISED	BY
CITY OF ANAHEIM DEPARTMENT OF PUBLIC WORKS						
PRIVATE STREET SECTIONS					STANDARD DETAIL NO.	
USE WITH STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION					162	
					SHEET 1 OF 1	